



规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

原材料: Raw material:

1. 塑胶: Plastic cement:
Hing Temperature Thermoplastics,
PBT White/ Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: SPCC/Copper Alloy C2680

电镀: Electroplate:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Talls
2. 外壳: Shell:
Nickel Plating

EAST-USB2QBX102X

1: 铁壳
2: 铜壳
B: 黑色
W: 白色

深圳市东方御业科技有限公司

WWW.DFYCONN.COM TEL:0755-27155560

品名 (ITEM NO)	USB A TYPE 双层全包式母座
料号 (PART NO)	EAST-USB2QBX102X
图号 (DWG NO)	EAST-UBF-126(1A)

页码 (SHEET)	1/1	单位 (UNIT):	MM
版本 (REV)	A/0	比例 (SCALE)	1:1
日期 (DATE)	2012.02.22		
设计 (DESIGN)	陈钦虎	未注公差 TOLERANCE UNSPECIFIED	
审核 (CHECKED)		X.X	±0.30
核准 (APPROVED)		X.XX	±0.25
		X.XXX	±0.15
		X°	±5°
		X.X°	±2°