



NOTES:

ELECTRICAL:

- VOLTAGE RATING: 125V AC.
- CURRENT RATING: 1.5A.
- CONTACT RESISTANCE: 30 mΩ MAX.
- INSULATION RESISTANCE: 500 MΩ MIN @ 500V DC.
- DIELECTRIC STRENGTH: 1000V AC 50Hz or 60Hz, 1MIN.

MECHANICAL:

- INSERT MATERIAL: UL94V-0.
- CONTACT MATERIAL: DIAMETER 0.46mm C51000(QSn+4-0), 3) PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
- SHIELD: 0.20mm THICKNESS H65Y BRASS NICKEL PLATED.
- MATING/UNMATING FORCE: 2.2KG.F MAX.
- RETENTION STRENGTH: 7.7KG.F MIN BETWEEN JACK AND PLUG.
- OPERATING LIFE: 750 CYCLES MIN.

ENVIRONMENTAL:

- STORAGE: -40°C ~ +85°C RELATIVE HUMIDITY<70%.
- OPERATION: -40°C ~ +85°C.

Remark:

- The mark with★is the key inspection dimension for QC.

CONTACTS (金針根數) : \_\_\_\_\_

1-1, 2, 3, 6 PIN: 8-8CONTACTS (8C)

LED STYLE (LED 顏色类型) : \_\_\_\_\_

1-L LED: GREEN, R LED: YELLOW (左綠右黃)

2-L LED: YELLOW, R LED: GREEN (左黃右綠)

8-L LED: GREEN, R LED: GREEN+YELLOW (左綠右綠黃)

9-L LED: GREEN, R LED: GREEN+YELLOW (左黃右綠黃)

PLASTIC(塑料) : \_\_\_\_\_

- PBT;
- NYLON66 (尼龙66) ;
- NYLON46 (尼龙46)

COLOR(顏色) : \_\_\_\_\_

1-BLACK (黑色) ; 2-WHITE (白色) ; 3-GRAY (灰色) ;

5-YELLOW (黃色) ; 7-GREEN (綠色) ; 8-BLUE (藍色)

GOLD PLATING(鍍金厚度) : \_\_\_\_\_

1-FU" : 2-1.5U" ; 3-3U" ; 4-6U" ;

5-15U" ; 6-30U" ; 7-50U"

# EAST-56A-31882021101

TOLERANCES UNLESS OTHERWISE SPECIFIED:	
X, X.X	± 0.38
X.XX	± 0.25
X.XXX	± 0.10
Angle	±1°

COSTOMER COPY		深州市东方御业科技有限公司	
WWW.DHYCONN.COM		TEL: 0755-27155560	
DRAWN: CHENLEI	2017/09/10	DATE: 2017/09/10	PART NO: EAST-56A-31882021101
CHECKED: CHENLEI	2017/09/10	DATE: 2017/09/10	SCALE: 1:1
APPROVED: QINXIAOYANG	2017/09/10	DATE: 2017/09/10	REV: (6-4S)

REV.	ECN NO.	MODIFY MATTER	DATE	APPROVED
A		RELEASE TO PRODUCTION		